




# Updates from beampipe vacuum studies at CERN

CARLO SCARCIA on behalf of the ET beampipe vacuum studies group at CERN

XIV ET Symposium, Maastricht, 06-10 May 2024

# CERN activities on ET beampipe vacuum



The main objectives are:

- **Coordinate the contributions** of all parties involved in the study of ET beampipes.
- Design, manufacture, assemble, and test a **pilot sector** of the selected ET beampipe vacuum systems.
- Preparing and writing the '**Technical Design Report**' for the vacuum systems of the ET's arms, including cost estimations.
- Contact and sharing of information with the **Cosmic Explorer community**.

# Conclusions from the 2<sup>nd</sup> ET annual meeting

XIII ET  
Symposium

2<sup>nd</sup> ET  
annual  
meeting

Objective  
from the 2<sup>nd</sup>  
annual  
meeting

- Ferritic alloys  
Mild steel and ferritic SS
- **Outperform 304/316L outgassing rates w/o requiring HT treatment.**
  - **Lower (>30%) raw material cost.**

**Identify optimal alloys and investigate pre-prototypes vacuum performance.**

**Finalization of the pre-prototypes vacuum tests.**

**Material/Vacuum**

Corrugated beampipe  
1-2 mm thick tube

- **No bellows & stiffeners.**
- **Low kg/m of material.**
- **Less current input if Joule effect bakeout.**

**Find a commercial partner for the pilot sector manufacturing.**

**Design finalization and procurement of the beampipe modules.**

**Design**

ET pilot sector

- **Location at CERN.**
- **Conceptual design.**
- **Preliminary measurement plan.**

**Site preparation and detailed design of the infrastructure/system**


**Peer review of the project, finalization of the design, and procurement.**

**Prototyping**

# Material/Vacuum: Overview of alternative alloys for beampipe

**Ferritic alloys**  
Mild steel and ferritic SS

- **Outperform 304/316L outgassing rates w/o requiring HT treatment.**
- **Lower (>30%) raw material cost.**



ASStS: Austenitic Stainless Steel, FSStS: Ferritic Stainless Steel, MS: Mild Steel. Vacuum Fired (950°C, 2h), Air baked (450 °C, 5d). Measurement error: ±40%; Detection limit: 50% of background

# Material/Vacuum: ET beampipe pre-prototypes

## System characteristics

DN400 – 2100 mm ( $t < 2$  mm)

AISI 304L-VF  
(AStS)

AISI 441  
(FStS)

S315MC  
(MS)


Pumping speeds scaled to ET conditions

## Objectives

Ultimate pressure after 80°C and 150°C bakeout

Verify water outgassing modelling

Test the effect of the increasing pumping speed during bakeout on ultimate pressure





AISI 441 corrugated chamber. Credit: CERN

# Material/Vacuum: ET beampipe pre-prototypes

## Water outgassing modelling


Modelling of effects of increased pumping speed during heating




# Material/Vacuum: ET beampipe pre-prototypes

## Water outgassing modelling

Modelling of effects of increased pumping speed during heating





We could exploit the use of NEG pumps [SAES proposal, 2010]





# Material/Vacuum: ET beampipe pre-prototypes


Simplified vacuum layout  
 150°C, 48h





# Material/Vacuum: ET beampipe pre-prototypes

Ultimate pressure after 80°C and 150°C bakeout



**As predicted, for all the chambers, ultimate pressures limited by instrumentation outgassing rates.**

**H<sub>2</sub> outgassing rate:  
< 8 10<sup>-14</sup> mbar l s<sup>-1</sup> cm<sup>-2</sup>**


(better estimation is not possible because of the intrinsic limitation of the system)

\* Improvement of the background contribution (RGA outgassing rate)

Orifice limited: 31 l s<sup>-1</sup> for H<sub>2</sub>, N<sub>2</sub> to H<sub>2</sub> conversion factor: 2.19, B-A gauge error: 15%. B-A: Bayard-Alpert, RGA: Residual Gas Analyser.

# ET beampipe pre-prototypes : conclusions

NEG assisted bake-out: 80°C - 7 days



**For all three chambers:**

- 1. Good matching between the model and experimental data.**
- 2. The model's predicted water partial pressure values generally align with the values from the mass spectrometer signal.**
- 3. The increase of pumping speed during the bakeout is proven to be a viable solution to shorten the duration.**

\*\* DN400 closing flanges erroneously fired before machining

# LoLA: Low outgassing Large Apparatus



## Measurements

After repeated 80°C, 48h (heating step)

- **Ultimate pressure & mass scan.**
- **H<sub>2</sub>, CH<sub>4</sub>, CO and CO<sub>2</sub> outgassing rates.**
- **Residual water outgassing rate.**

## Main objectives


- **Track the evolution of water outgassing rate after low-temperature long-duration bakeout.**
- **Extrapolate outgassing rates model for ferritic alloys.**

## Pumping speed

**Pumping speeds not scaled to an ET sector**



# LoLA: Materials and dimensions



P355N 16m chamber. Credit: CERN



AISI 441 chambers. Credit: CERN

## Materials and dimensions

### Mild steel chamber

Chamber material: **P355N**

Final chamber dimensions: **Ø219 x 6 mm - 16 m**

Closing flanges [DN250]: S355J2+N (forged)

**UNDER TEST**

### Ferritic StS. chamber


Chamber material: **AISI 441**

Final chamber dimensions: **Ø80 x 2 mm - 15 m**

Closing flanges [DN100]: AISI 316LN (VF)

**UNDER CONSTRUCTION**


# LoLA: mild steel chamber ultimate pressure after bakeout



**Good agreement** between the experimental data and the model.


Orifice limited: 19.5 l s<sup>-1</sup> for H<sub>2</sub>O, B-A gauge error: 15%. The measurements are done at 294K.

# LoLA: mild steel chamber mass scan after bakeout



SEM scan taken 24h after B-A gauges were off (48h from cooldown).

# LoLA: mild steel chamber outgassing rates after bakeout



**H<sub>2</sub>O specific** outgassing rates can be **extrapolated** from throughput and accumulation measurements.


CO and CO<sub>2</sub> outgassing rates after the first heating step compete with H<sub>2</sub> one.

**PRELIMINARY ANALYSIS**

Measurement error: ±40% (estimated). The measurements are done at 294K.



# LoLA: mild steel chamber outgassing rates after bakeout




**H<sub>2</sub> outgassing rates are in line with preliminary requirements from ET CDR 2020**

**Next main step: understand the desorption mechanism and model**

Measurement error: ±40% (estimated). The measurements are done at 294K.

# LoLA: Preliminary considerations on mild steel chamber results

Low temperature (80°C) bakeout was discussed with Cosmic Explorer colleagues as potential cost saving solution. However...



\*DC bakeout, insulation: mineral wool, thickness: 15 cm

# ET pilot sector

The pilot sector aims to **test the design, fabrication, installation and commissioning** of the proposed **beampipes and support system**. It also aims to compare the feasibility of a selected number of technical choices.

**Q1 2024 (January)**


**Project peer reviewed** (international experts panel) with recommendations.

**Q2-Q4 2024**

**Manufacturing and procurement** of the **ancillary components/equipment**.

**From Q4 2024/Q1 2025**


Start of installation of a  
AISI 441 VIRGO-like pipe  $\varnothing$  **1.08 m x 4 mm x 36 m**



# ET pilot sector

Preliminary tests/verifications/validations :

- Installation and alignment of supports and beampipes.
- In-situ welding and assembly.
- Integration of thermal insulation, instrumentation and vacuum components.
- Leak detection procedure during fabrication and assembly.
- Pumpdown time.
- Bakeout: temperature distribution and efficiency.
- Ultimate partial pressures and outgassing rates.
- Validate the calculated vibration transmission matrix.
- Efficiency of the methods used to reduce the quantity of dust



*Courtesy of M. Dakshinamurthy and A. T. Pérez*


3 segments of 850 mm diameter, 500 mm length  
(rolled & welded cylinders)

Mock-up to test welding process and parameters optimization for reduction of potential virtual leaks (fabrication to be completed early Q3, NDTs and leak detection will follow)

# ET pilot sector

Preliminary tests/verifications/validations :


- Installation and alignment of supports and beampipes.
- In-situ welding and assembly.
- Integration of thermal insulation, instrumentation and vacuum components.
- Leak detection procedure during fabrication and assembly.
- Pumpdown time.
- Bakeout: temperature distribution and efficiency.
- Ultimate partial pressures and outgassing rates.
- Validate the calculated vibration transmission matrix.
- Efficiency of the methods used to reduce the quantity of dust.



3D model of the pumping module

# ET pilot sector: vacuum system

## Vacuum measurement sequence: Four steps



# ET pilot sector: vacuum system

## Preliminary experimental programme (2024)

Conditioning and outgassing rate measurements of all the valves, instrumentation, flanges and non-ferritic StS components (Q2-Q3 2024).

Design of the leak detection measurement/campaign (Q2-Q4 2024)

Outgassing rate measurements of baffle's material surface treatments and coatings (Q2-Q3 2024) [in collaboration with IFAE].

Detailed measurement procedure to be written before Q4 2024.

	2023				2024				2025				2026			
	Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4
TDR writing																
Material removal and cleaning of hosting building																
Installation of services (WiFi, electricity)																
Design of support and beampipes																
Design of tooling																
Design of bakeout system, cabling and instrumentation racks																
Place orders for all required material																
Manufacturing, reception tests and cleaning																
Manufacturing and delivery of the baffles																
Assembly and leak detection																
Test programme																



# ET pilot sector: peer review recommendations

Recommendation	Action
Investigation on corrosion resistance of ferritic stainless steels (tunnel environmental conditions)	Contract with UGhent to be launched for comparative corrosion studies
Use pilot sector as testbed for extrapolation of ET leak detection	Methodologies and tooling under investigation
ET pilot sector to be used to test different insulation materials and solutions (installation, removal)	Contact with companies started
Implementation of large gate valves (DN1000+) to test thermal cycling, stroke cycling, treatments etc.	See Luigi's presentation
Implementation of temperature control systems in selected building	
Consider launching a parallel test on a corrugated chamber (perhaps through external contribution)	




[home.cern](http://home.cern)

# Summary of design/material/vacuum

	<b>PILOT SECTOR</b> <b>FEASIBLE NOW</b> (+) Lower cost (+) No HTT required	Industrial feasibility <b>TBC</b> <b>PREFERRED</b> (+) Much lower cost (+) No HTT required	(-) Higher cost	
<b>Ferritic AISI 441</b>				
<b>Mild Steel S315</b>	(+) Lower cost (+) No HTT required (-) Surface corrosion ?	(+) Much lower cost (+) No HTT required (-) Surface corrosion ?	(+) Much lower cost (+) No HTT required (-) Surface corrosion ?	<b>Surface corrosion                  resistance TBE</b>
<b>Austenitic AISI 304L</b>	(+) Proven solution (-) HTT required	(-) HTT required	(-) Higher cost (-) HTT required	
	<b>Smooth pipe/stiffeners                  Virgo like 3-4 mm</b>	<b>Corrugated                  1.5 – 2 mm</b>	<b>Pipeline                  &gt; 5 mm</b>	


HTT - High Temperature Treatment  
 Costs - relative to the Virgo like baseline.

# Joule bakeout @ CERN




Power supply max current: 400A

# Joule bakeout @ CERN



Chamber:  
AISI 441 (400 x 1.5 x 2050 mm)




Max temperature according to heat transfer model: 64°C  
Max recorded temperature: 66°C

# ET pilot sector vacuum layout

## Measurement sequence

Reduced system (background)



Note:

EC, bellows and PM  
bakeout with heating  
jackets, tapes, and collars.

### Step 1

Instrumentation, valves,  
and all pumps mounted.

#### Measurements

- Ultimate pressure and tot. outgassing rate.
- Isothermic measurements.

### Step 2

Instrumentation, valves,  
and all pumps removed (VF  
flanges mounted)  
but mobile pumping group.


#### Measurements

- Accumulations for specific outgassing rates assessment (H<sub>2</sub>, CH<sub>4</sub>, CO and CO<sub>2</sub>).
- Isothermic measurements.

# ET pilot sector vacuum layout

## Measurement sequence

### Full system (chamber)



Note:

ECs, bellows and PMs bakeout with heating jackets, tapes, and collars.

Chamber heated by joule effect.

### Step 3

Instrumentation, valves, and all pumps **not yet mounted** but mobile pumping group.

#### Measurements

- Accumulations for specific outgassing rates assessment ( $H_2$ ,  $CH_4$ , CO and  $CO_2$ ).
- Isostatic measurements.

### Step 4

Instrumentation, valves, and all pumps mounted.


#### Measurements

- Ultimate pressure and tot. outgassing rate.
- Isostatic measurements.



# ET pilot sector vacuum layout

## Instrumented End Cap (EC)




### Component

- ① B-A gauge [DN63]
- ② RGA [DN63]
- ③ 4-way cross [DN40]
- ④ Variable leak valve [DN40]
- ⑤ Venting valve + dust filter [DN40]
- ⑥ Capacitance gauge [DN40]
- ⑦ Angle valve [DN40]
- ⑧ SRG [DN40]
- ⑨ Viewport for future laser [DN100]

# ET pilot sector vacuum layout

## Pumping Module (PM)



### Component

- ① TMP group
- ② Angle valve [DN63]
- ③ NEG pump [DN150]
- ④ Gate valve [DN150]
- ⑤ Sputter Ion pump [DN100]
- ⑥ Gate valve [DN100]
- ⑦ Silicon wafer port [DN100]
- ⑧ Viewport [DN63]

Pumping speeds scaled to an ET sector  
( $P_{\max}$  pilot sector =  $P_{\max}$  middle point between two pumps in ET)